

Levor Mosaic wooden tiles are made from natural, thermally-treated wood, adhering to modern aesthetic and ecological principles. For a long-lasting, moisture-resistant finish, the tiles are coated with a protective layer of oil-wax polish made in Germany by Osmo. These treatments allow Levor Mosaic tiles to be used throughout the house, from tiling walls and columns, to kitchen islands and backsplashes.

As a design element, Levor Mosaic combines easily with ceramic tiles. The Mosaic's plastic mesh backing allows it to conform to the contours of the surface beneath.

The Ash, Bird Cherry, and Oak varieties of Levor Mosaic can be installed as flooring and staircase treads and risers using the standard procedure.

Installation and care:

While Levor Mosaic tiles are moisture-resistant, they should not be installed in areas continuously exposed to water, for example, as shower wall tiles.

1. The tiles should be kept at room temperature for at least 48 hours before installation.
2. To install the tiles, use a non-water based urethane wood flooring adhesive with moisture vapor protection. Water-based adhesives should NOT be used.
3. For subsequent filling of seams, use non-sanded grout, one-component polyurethane sealant, or acrylic caulk in a suitable color. The grout can be applied once the adhesive has dried (approximately 24 hours).
4. Suitable adhesives and grout are available from companies such as Titebond, TEC, Custom Building Products, and Laticrete.

To clean the mosaic tiles, wipe with a damp cloth. Avoid using cleaning solvents to prevent damage to the wood finish.

For more information, please visit us at www.LevorWood.com

LEVOR

MOSAIC